



Data Express® DX115

APPLICATIONS:

- Drive Swapping
- Drive Transporting
- Security
- Backup
- Testing
- Audio/Video Editing

EASY INSTALLATION



Insert any capacity 3.5" SAS/SATA HDD into the removable carrier



Install Data Express receiving frame into any standard 5.25" bay



Insert carrier into frame, turn on key lock & press power button

Compact & Rugged Removable Drive Enclosure



Data Express

- ▶ **Supports 3.5" Serial Attached SCSI (SAS) or Serial ATA (SATA)***
- ▶ **SAS Receiving Frame is Compatible with SATA Drive Carrier**
- ▶ **Reliable Steel Construction**
- ▶ **Drive Carrier Key Lock & HDD Activity Indicator**

| Features | Benefits |
|--|---|
| Centered Drive Carrier Design | Fits Standard & Custom 5.25" PC Bay |
| SAS Frame is Compatible w/ SATA Carriers | Accepts Both SATA & SAS Drives |
| 25K Insertion Rating | Connectors Support Many Insertions & Removals |
| "Soft Start" Circuitry | Eliminates Current In-Rush/Assures Data Integrity |

*Hard Drive Sold Separately



Data Express DX115



DX115 SATA 3G

| Part Number | Description |
|----------------|--|
| 6606-5000-0500 | Complete Assembly, SATA 3G, Fan, RoHS, Black |
| 6607-7100-0500 | Carrier, SATA 3G/SAS, Black |
| 6608-5000-0500 | Receiving Frame, SATA 3 G, Fan, RoHS, Black |

DX115 SAS/SATA

| Part Number | Description |
|----------------|--|
| 6606-7000-0500 | Complete Assembly, SAS, Fan, RoHS, Black |
| 6607-7100-0500 | Carrier, SATA 3G/SAS, RoHS, Black |
| 6608-7000-0500 | Receiving Frame, SAS, Fan, RoHS, Black |

Accessories

| Part Number | Description |
|----------------|--|
| 6004-9901-0500 | Hard Shell Carrying Case for any Data Express or DataPort Product |
| 3800-350-01 | Small Carrying Case for any Data Express or DataPort Carrier, 9"L x 3"D x 8"W (inch) |
| 3800-525-01 | Large Carrying Case for any Data Express or DataPort Product, 1"L x 4"D x 9"W (inch) |
| CC-500-02 | Metal Carrying Case with Lock, Anti-Static Foam Padding |

Specifications:

- Minimum dimensions and centered-carrier design; fits into any standard or custom 5.25" PC bay
- SAS receiving frames can accept SATA drive carriers for added flexibility and cost effectiveness
- Rugged construction; drive is protected in the event of physical trauma
- Mating connectors provide 25K insertion rating for multiple insertions and removals
- Exceeds rotational vibration and heat dissipation requirements of today's high-speed drives
- "Soft Start" circuitry assures data integrity by eliminating in-rush current during spin-up and preventing power arcing during insertion
- Integrated fan assures proper drive cooling
- Drive carrier key lock
- Key lock functions independently from drive power
- Power, spin and fan failure indicator
- 5 year warranty

Design:

- Dimensions - 5.81" W x 8.08" L x 1.62" H (inches)
- Weight 3.80 lbs.



Options:



Hard-Shell Carrying Case
6004-9901-0500



Soft-Sided Carrying Case
3800-350-01 sm.
3800-525-01 lg.



All-Metal Carrying Case
CC-500-02