










	<h2 style="text-align: center;">CRU-DataPort® Enclosures Matrix</h2>										
											
<u>Supported Interfaces</u>	eSATA (2 HDD) Enclosure	eSATA (4 HDD) Enclosure	SATA (2 HDD) Enclosure	SATA (4 HDD) Enclosure	4 Bay Mini Subsystem	2 Bay Enclosure	4 Bay Enclosure	7 Bay Enclosure	USB/eSATA Enclosure	HotDock Enclosure	1U Enclosure
40-Pin IDE Ultra ATA 33/66/100/133									✓	✓	
68-Pin or 80-Pin Ultra 320 SCSI LVD SCA-2 (320 MB/s)						68-Pin only	68-Pin only	68-Pin only			
Serial ATA 3.0 Gb/sec	✓	✓	✓	✓	✓				✓	✓	✓
SAS capability			✓	✓	✓						
<u>Sizes/Speeds Supported</u>											
5.25" Half Height	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
HDD RPM Speed Supported	10000	10000	10000	10000	7200	10000	10000	10000	7200	7200	7200
<u>Features</u>											
SCSI ID Selector						✓	✓	✓			
Number of Fan(s)	4	6	4	6	2	1	2	2	1	1	4
Power Supply	Auto sensing 110V/220V	Switchable 110V/220V	Auto sensing 110V/220V	Switchable 110V/220V	Switchable 110V/220V	Auto Sensing 110V/220V	Switchable 110V/220V	Switchable 110V/220V	AC Adapter	AC Adapter	Switchable 110V/220V
Available in Black	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Available in White	✓	✓	✓	✓		✓	✓	✓			
<u>Specifications</u>											
Internal Cables as accessory or kit	A shielded 200 (PN 7356-500-01) or 390mm (PN 7356-500-02) SATA cable per HDD	A shielded 200 (PN 7356-500-01) or 390mm (PN 7356-500-02) SATA cable per HDD	A shielded 200 (PN 7356-500-01) or 390mm (PN 7356-500-02) SATA cable per HDD	A shielded 200 (PN 7356-500-01) or 390mm (PN 7356-500-02) SATA cable per HDD	A shielded 150mm (PN 7356-500-03) or for non removable unit (PN 7356-500-02) SATA cable per HDD	NA	NA	NA	NA	NA	A shielded 100mm or 300mm SATA cable per HDD
External Cables as accessory or kit	Shielded 1M eSATA cable per HDD; (PN 7366-007-02)	Shielded 1M eSATA cable per HDD; (PN 7366-007-02)	1Meter InfiniBand SFF8470; (7366-700-03) or InfiniBand to mini SAS SFF8088 (PN 7366-701-01)	1Meter InfiniBand SFF8470; (7366-700-03) or InfiniBand to mini SAS SFF8088 (PN 7366-701-01)	Shielded 1M eSATA cable per HDD; (PN 7366-007-02)	1M bundled/shielded with VHDC to HDC (PN 7366-001-01)	1M bundled/shielded with VHDC to HDC (PN 7366-001-01)	1M bundled/shielded with VHDC to HDC (PN 7366-001-01)	USB or eSATA cable	USB or eSATA cable	1Meter InfiniBand SFF8470; (7366-700-03) or InfiniBand to mini SAS SFF8088 (PN 7366-701-01)
Host Adapter Brackets	Host Adapter (PN 7100-800-00) or (PN 7100-800-10)	Host Adapter (PN 7100-800-00) or (PN 7100-800-10)	Host Adapter (PN 7100-800-00) or (PN 7100-800-10)	Host Adapter (PN 7100-800-00) or (PN 7100-800-10)	Host Adapter (PN 7100-800-00) or (PN 7100-800-10)	NA	NA	NA	NA	NA	Host Adapter (7100-800-00)
Supported RAID Levels	JBOD, RAID 0, 1, 10	JBOD, RAID 0, 1, 10, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 10, 5	JBOD, RAID 0, 1, 10, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5	JBOD, RAID 0, 1, 5	NA	NA	JBOD, RAID 0, 1, 10, 5
Compliance	FCC/CE/UL	FCC/CE/UL	FCC/CE/UL	FCC/CE/UL	FCC/CE/UL				CE		FCC/CE/UL
<u>Construction</u>											
Carrier	DP 5+	DP 5+	DP 10 or DX 115	DP 10 or DX 115	DP25	Mounting kit MK35/525 HD-R	Mounting kit MK35/525 HD-R	Mounting kit MK35/525 HD-R	NA	DP 10	DP 10
Frame					DP25				NA	Metal	Metal
Enclosure Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Metal	Plastic	Plastic	Metal
<u>Reliability</u>											
Warranty	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year	1 year
25K Connector Insertion Rating	✓	✓	✓	✓	✓					✓	✓

Note: Contact CRU Sales for further details on evaluation and test setup